



Serving The Leather Industry Since 1887

■ WAREHOUSE ■ MILWAUKEE ■ NEWARK ■

142 Lockwood Street, Newark, New Jersey 07105 USA  
Phone (973) 589-2002 • Fax (973) 589-7377 • [www.atlasrefinery.com](http://www.atlasrefinery.com)

## ATLAS<sup>®</sup> LEATHER OIL-88

Atlas Leather Oil-88 is a synthetic oil-based oiling-off system for crust leather, which provides a rich surface lubrication, pull-up effect and enhanced water resistance.

### TYPICAL ANALYSIS:

Appearance	Liquid
Moisture Content	Nil
Lbs./Gallon	7.80+/-0.05

### PRODUCT CARE:

Solubility:	Insoluble in water, miscible in solvents & oils.
Handling:	Handle as any non-hazardous oil. Mix well before use.
Storage:	Optimum performance and shelf life are maintained when stored near room temperature. Keep from freezing or overheating.
Shelf Life:	12 months when properly stored.

### APPLICATION:

The recommended use level of Atlas Leather Oil-88 is 14-22 grams/ft<sup>2</sup> when roll coating, spraying or brushing. After piling overnight it imparts a rich surface feel, pull-up effect and dynamic water resistance (17-20,000 flexes minimum) when using the Maeser test method. No dilution is required. For optimal results a thorough testing is recommended. Atlas Leather Oil-88 is useful for tackifying baseball glove and golf club handle leathers.

ALL DATA AND RECOMMENDATIONS HEREIN ARE ACCURATE AT THE TIME OF PUBLICATION AND ARE FOR GUIDANCE ONLY; WE CANNOT BE HELD RESPONSIBLE IN ANY WAY WHAT SO EVER. ATLAS REFINERY, INC. RESERVES THE RIGHT TO MODIFY THEM WITHOUT NOTICE. WORK CONDITIONS AND TYPE OF RAW MATERIAL CAN AFFECT THE FINAL RESULTS. IT IS THE RESPONSIBILITY OF THE USER TO APPLY THE RECOMMENDATIONS TO THE ACTUAL CONDITIONS AND PARTICULAR PURPOSE.