



Serving The Leather Industry Since 1887

■ WAREHOUSE ■ MILWAUKEE ■ NEWARK ■

142 Lockwood Street, Newark, New Jersey 07105 USA
Phone (973) 589-2002 • Fax (973) 589-7377 • www.atlasrefinery.com

ATLAS[®] LEATHER OIL-90

Atlas Leather Oil-90 is an oiling-off compound for chrome and vegetable tanned leathers where two-tone effect for 'pull-up' is desired. It has also shown good water resistance on leathers.

TYPICAL ANALYSIS:

Appearance	Clear Liquid
Moisture Content, %	Nil
Lbs./Gallon	7.5+/-0.05

PRODUCT CARE:

Solubility:	Insoluble in water, miscible in solvents & oils.
Handling:	Handle as any non-hazardous oil. Mix well before use.
Storage:	Optimum performance and shelf life are maintained when stored near room temperature. Keep from freezing or overheating.
Shelf Life:	12 months when properly stored.

APPLICATION:

Atlas Leather Oil-90 is applied on the grain side of the leather by roller coating, curtain coating, swabbing, spraying or any other well known method of application. The quantity of use depends upon the softness and degree of "pull-up" effect that is desired. For most applications, 15-30 grams/ft² of Atlas Leather Oil-90 are recommended to impart a nice two-tone pull-up effect and the enhancement of water resistant properties.

ALL DATA AND RECOMMENDATIONS HEREIN ARE ACCURATE AT THE TIME OF PUBLICATION AND ARE FOR GUIDANCE ONLY; WE CANNOT BE HELD RESPONSIBLE IN ANY WAY WHAT SO EVER. ATLAS REFINERY, INC. RESERVES THE RIGHT TO MODIFY THEM WITHOUT NOTICE. WORK CONDITIONS AND TYPE OF RAW MATERIAL CAN AFFECT THE FINAL RESULTS. IT IS THE RESPONSIBILITY OF THE USER TO APPLY THE RECOMMENDATIONS TO THE ACTUAL CONDITIONS AND PARTICULAR PURPOSE.