



Serving The Leather Industry Since 1887

■ WAREHOUSE ■ MILWAUKEE ■ NEWARK ■

142 Lockwood Street, Newark, New Jersey 07105 USA  
Phone (973) 589-2002 • Fax (973) 589-7377 • [www.atlasrefinery.com](http://www.atlasrefinery.com)

## ATLAS® LEATHER OIL-FM

Atlas Leather Oil-FM is a finishing oil specially designed as a hand feel modifier. FM makes a very light pull up without high-lighting the defects, and has a draggy feel.

### TYPICAL ANALYSIS:

Appearance	Reddish amber viscous liquid
Moisture Content, %	Nil
Lbs./Gallon	8.7+/-0.05

### PRODUCT CARE:

Solubility:	Insoluble in water, miscible in solvents but most commonly mineral spirits or glycols.
Handling:	Handle as any non-hazardous fatliquor. Bring to room temperature. All fatliquors are emulsions and may separate over time. This is normal. Mix well before use, and they will perform properly.
Storage:	Optimum performance and shelf life are maintained when stored near room temperature. Keep from freezing or overheating.
Shelf Life:	12 months when properly stored.

### APPLICATION:

Atlas Leather Oil-FM is applied on the grain side of the leather by roller coating. FM may be used by itself or in combination with other Atlas leather oils and Atlasene JD, TA, TC, 100 or M.

Continued on reverse...

The quantity of use depends upon the feel and degree of “pull-up” effect desired. For most applications, 6-14 grams/ft<sup>2</sup> of Atlas Leather Oil-FM based on crust weight is recommended.

ALL DATA AND RECOMMENDATIONS HEREIN ARE ACCURATE AT THE TIME OF PUBLICATION AND ARE FOR GUIDANCE ONLY; WE CANNOT BE HELD RESPONSIBLE IN ANY WAY WHAT SO EVER. ATLAS REFINERY, INC. RESERVES THE RIGHT TO MODIFY THEM WITHOUT NOTICE. WORK CONDITIONS AND TYPE OF RAW MATERIAL CAN AFFECT THE FINAL RESULTS. IT IS THE RESPONSIBILITY OF THE USER TO APPLY THE RECOMMENDATIONS TO THE ACTUAL CONDITIONS AND PARTICULAR PURPOSE.