



Serving The Leather Industry Since 1887

■ WAREHOUSE ■ MILWAUKEE ■ NEWARK ■

142 Lockwood Street, Newark, New Jersey 07105 USA
Phone (973) 589-2002 • Fax (973) 589-7377 • www.atlasrefinery.com

ATLAS® LEATHER OIL-SW

Atlas Leather Oil-SW is an oiling-off compound for chrome and semi chrome leathers to promote oil pull up and feel while maintaining water resistance. SW may be applied to full grain, nubuck and splits.

TYPICAL ANALYSIS:

Appearance	Amber colored liquid
Moisture Content, %	1.0 Max
Lbs./Gallon	8.2

PRODUCT CARE:

Solubility:	Dispersible in water, miscible in mineral spirits.
Handling:	Handle as any non-hazardous fatliquor. Bring to room temperature. All fatliquors are emulsions and may separate over time. This is normal. Mix well before use, and they will perform properly.
Storage:	Optimum performance and shelf life are maintained when stored near room temperature. Keep from freezing or overheating.
Shelf Life:	12 months when properly stored.

APPLICATION:

Atlas Leather Oil-SW is applied on the grain side of the leather by roller coating or curtain coating at 50°C. It can be used

Continued on reverse...

alone, or diluted with different suitable solvents, depending upon the pull up effect required. It can be also be used together with other oils as a feel modifier. For waterproof leathers, it can be used by itself, or with other oils or waxes that have no effect on the waterproofness of the leather. For most applications, 6-14 grams/ft² of Atlas Leather Oil-SW based on crust weight is recommended.

ALL DATA AND RECOMMENDATIONS HEREIN ARE ACCURATE AT THE TIME OF PUBLICATION AND ARE FOR GUIDANCE ONLY; WE CANNOT BE HELD RESPONSIBLE IN ANY WAY WHAT SO EVER. ATLAS REFINERY, INC. RESERVES THE RIGHT TO MODIFY THEM WITHOUT NOTICE. WORK CONDITIONS AND TYPE OF RAW MATERIAL CAN AFFECT THE FINAL RESULTS. IT IS THE RESPONSIBILITY OF THE USER TO APPLY THE RECOMMENDATIONS TO THE ACTUAL CONDITIONS AND PARTICULAR PURPOSE.